

Item no.: 356370

SafeStream Gigabit Multi-WAN VPN Router

155,66 EUR

Item no.: 356370
shipping weight: 1.40 kg
Manufacturer: TP-LINK

Product Description

Professional VPN router with load balancing and central SDN integration.

- Integrated with Omada SDN : Zero-Touch Provisioning (ZTP) **, centralised cloud management and intelligent network monitoring
- Centralised management : Cloud access and Omada app provide convenient and easy management
- Gigabit ports : 1 Gigabit SFP and 5 Gigabit RJ45 ports provide high-speed wired connections
- Up to 4 WAN ports : Load balancing with up to 4 Internet access points, 1x Gigabit SFP WAN port, 1x Gigabit RJ45 WAN port and 2x Gigabit WAN / LAN ports enables a bundled, optimally utilised and fail-safe Internet connection
- High-security VPN : Supports up to 100 x LAN-to-LAN IPSec, 50 x OpenVPN * - , 50 x L2TP and 50 x PPTP VPN connections
- Numerous security features : Advanced firewall policies, DoS defence, IP / MAC / URL filtering and other security features protect your network and data

HARDWARE FUNCTIONS

- Standards and protocols
- IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1q
- TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, OpenVPN, SNMP
- Interface
- 1 fixed Gigabit SFP WAN port
- 1 fixed gigabit RJ45 WAN port
- 2 fixed Gigabit RJ45 LAN ports
- 2 exchangeable Gigabit RJ45 WAN/LAN ports
- Cable
- 10BASE-T: UTP category 3, 4, 5 cable (max. 100 m) EIA/TIA-568 100 ? STP (max. 100 m)
- 100BASE-TX: UTP cable of categories 5, 5e (max. 100 m) EIA/TIA-568 100 ? STP (max. 100 m)
- 1000BASE-T: UTP cable of categories 5, 5e, 6 (max. 100 m)
- Reset button
- Power supply 100-240 V~50/60 Hz
- Flashing SPI 4 MB + NAND-128 MB
- DRAM 512 MB
- LED PWR, SYS, SFP WAN, WAN (speed, link/act), LAN (speed, link/act)
- Dimensions (W*D*H) 226 x 131 x 35 mm

OTHER

- Certification CE, FCC, RoHS
- Package contents
- ER7206
- IEC power cable
- Quick installation guide
- System requirements Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7/8/8.1/10, MAC OS, NetWare, UNIX or Linux
- Operating temperature: 0-40 ? (32-104 ?);
- Storage temperature: -40-70 ? (-40-158 ?)
- Operating humidity: 10-90% RH non-condensing
- Storage humidity: 5-90% RH non-condensing

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

