

Item no.: 384589

CSM-200-1218 - unmanaged 10/100BaseT(X) to 100BaseFX plug-in modules for the NRack system

from 284,35 EURItem no.: 384589
shipping weight: 0.20 kg
Manufacturer: MOXA

Product Description

The CSM-200 plug-in media converters from Ethernet to fibre optic are designed for the NRack System™. The modules provide media conversion from 10/100BaseT(X) to 100BaseFX (SC/ST connectors) and can be installed in any NRack System™ enclosure. Ethernet interface- 10/100BaseT(X) ports (RJ45 connector): 1- 100BaseFX ports (single-mode SC connector): CSM-200-1218: Single-mode SC connector- Magnetic insulation protection: 1.5 kV (built-in)- Standards: IEEE 802.3u for 100BaseT(X) and 100BaseFX- Fibre optic Performance parameters- Input current: 180 mA @ 12 VDC- Input voltage: 12 VDC- Overload current protection: Supported- Power consumption: 180 mA @ 12 VDC Physical properties- Dimensions: 86.8 x 124.3 x 21 mm (3.42 x 4.89 x 0.83 in.)- Weight: 125 g (0.28 lb) Environmental Conditions- Operating Temperature: 0 to 55°C (32 to 131°F)- Storage Temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- EMC: EN 55032/24- EMI: CISPR 32, FCC Part 15B Class A- Safety: EN 60950-1, UL 60950-1- Vibration: IEC 60068-2-6 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV(AC), 1 kV(DC)- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Environmental testing- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3 MTBF- Time: 1.454,560 hours- Standards: Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

