

Item no.: UVC-G4-PRO-3\_EU

## UVC-G4-PRO-3 - Professional Indoor/Outdoor Camera, 4K Video, 3-Pack

# from **1.619,37 EUR**

Item no.: UVC-G4-PRO-3\_EU shipping weight: 2.10 kg Manufacturer: Ubiquiti



### Product Description

Ubiquiti UVC-G4-PRO-3 - Professional Indoor/Outdoor Camera, 4K Video, 3-PackPLEASE NOTE: THIS IS A 3-PACK. The UniFi(R) Protect Camera, model UVC-G4-PRO, represents the next generation of cameras designed for use with the UniFi Protect surveillance management system. This camera offers 4K Ultra HD resolution for day or night use and integrates with the UniFi Protect software for powerful and flexible IP video management.

The UVC-G4-PRO is easy to set up, operate, and manage using the UniFi Protect software, which comes pre-installed on the UCK-G2-PLUS, the latest generation Cloud Key controller. Features

The G4 Pro camera features a powered zoom lens and crisp 4K Ultra HD video performance with infrared capability. The versatile 3-axis mount enables indoor or outdoor installation of the camera. The camera has infrared LEDs with an automatic IR cut filter for day and night surveillance.

- 4K Ultra HD (3840 x 2160), 24 FPS
- F 4.24 12.66 mm, /1.53 /3.3
- Wide-angle/zoom lens
- OS08A20 sensor, 1/1.8"
  IP67-rated weather resistance
- Enhanced low-light performance
- Integrated high-power infrared LEDs
  802.3af/802.3at support
- Built-in microphoneWall, ceiling, or pole mount

- Dimensions (without mounting plate): 86 x 153 mm ( 3.39 x 6.02")
  Weight (without mounting plate): 700 g (1.54 lb)
  Networking interface: (1) 10/100/1000 Ethernet port
  Management interface: Managed mode: UniFi Protect; Standalone mode: Camera integrated web UI Sensor: OS08A20, 1/1.8" Lens: F 4.24 - 12.66 mm; /1.53 - /3.3
- Night mode IR LEDs with mechanical IR cut filter

- Night mode IR LEDs with mechanical IR cut filter
  Microphone: Yes
  Button: Factory reset button
  Power method: IEEE 802.3af/at
  Power supply: 802.3af/802.3at or UniFi PoE switch
  Maximum power consumption: 12.5 W
  Mounting: Wall/ceiling/pole
  Operating temperature: -20°C to 50°C (-4°F to 122°F)
  Operating Humidity: 0 to 90% non-condensing
  Weatherproofing: IP67

#### Video

- Video compression: H.264
  Resolution: 4K Ultra HD (3840 x 2160)
  Maximum frame rate: 24 FPS
- Image settings: Flip, brightness, contrast, WDR, hue, infrared, sharpness,
- saturation, denoise, 50/60 Hz flicker reduction

• Viewing angle: Wide: 108° (H), 58° (V), 125° (D); Zoom: 37° (H), 20° (V), 43° (D)

PLEASE NOTE: THIS IS A 3-PACK.

## **Specifications**

Scan this QR code to view the product All details, up-to-date prices and availability

