

Item no.: UISP-CABLE-PRO

UISP-CABLE-PRO - Patchcable Cat.5, SF/UTP, 305m, black

from **138,88 EUR**

Item no.: UISP-CABLE-PRO

shipping weight: 11.89 kg

Manufacturer: Ubiquiti



Product Description

UISP-Cable-Pro - Industrial-grade Ethernet Cat. 5e Cable, 305 m

The UISP-Cable-Pro is a Category 5e cable with a highly insulating, weatherproof jacket that prevents damage from rain, snow, and other extreme climatic conditions. The cable is also fortified with internal foil shielding and a drain wire that collectively shield it from electrostatic discharge (ESD) and allow it to maintain Gigabit Ethernet link rates even when electromagnetic interference is present.

- Box dimensions: 330 x 330 x 340 mm
- Box weight: 12 kg
- Cable length: 305 m (1000 ft)
- Cable color: Black
- Cable type: Cat. 5e, shielded
- Ethernet support: Up to 1 Gbps
- Conductor wire gauge: 24 AWG
- Conductor: Solid bare copper
- Conductor diameter: 0.500 +/- 0.005 mm
- Insulation type: Solid polyethylene
- Insulation thickness: Avg. 0.26 mm; Min. 0.25 mm
- Insulation diameter: 1.04 +/- 0.03 mm
- Separation (polyester wrapping): Thick: 0.025 mm; Extent: 20 mm
- Anti-crosstalk divider: None
- Cable shield (aluminum foil): Thick: 0.060 mm; Extent: 18 mm
- ESD drain wire: 0.4 CCS
- Rip cord: Yes
- Jacket material: Polyethylene
- Jacket thickness: Avg. 0.50 mm; Min. 0.46 mm
- Jacket outer diameter: 6.0 +/- 0.30 mm
- Jacket color: Black
- Storage temperature: -30°C to 75°C (-22°F to 167°F)
- Installation temperature: -20°C to 60°C (-4°F to 140°F)
- Operation temperature: -40°C to 80°C (-40°F to 176°F)
- Standards: ANSI/TIA-568-C.2 (2009); ISO/IEC 11801 (Edition 2.2)

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

