

Item no.: USW-FLEX-XG

## USW-FLEX-XG - Switch Flex XG, Multi-Gigabit Layer-2 Switch

# 314,60 EUR

Item no.: USW-FLEX-XG  
 shipping weight: 1.20 kg  
 Manufacturer: Ubiquiti



### Product Description

#### USW-Flex-XG - Switch Flex XG

The Switch Flex XG (USW Flex XG) is a fully managed, multi-Gigabit, Layer-2 switch with (4) 10 GbE RJ45 ports and (1) GbE PoE input. The USW Flex XG sports slim, compact housing and can be mounted on a desktop. This switch can also be monitored or configured from anywhere with the powerful, intuitive UniFi Network web application and mobile app.

Features:

- (1) GbE, 802.3at PoE+ RJ45 input
- (4) 10 GbE RJ45 ports
- Compact, slim housing
- Can be powered with a 5V, 5A USB-C adapter

#### Mechanical

- Dimensions: 135 x 185 x 32 mm (5.31 x 7.28 x 1.27")
- Weight: 1.2 kg (2.65 lb)
- Enclosure material: Polycarbonate

#### Hardware

- Total non-blocking throughput: 41 Gbps
- Switching capacity: 82 Gbps
- Forwarding rate: 61.012 Mpps
- Max. power consumption: 25 W
- Power method: (1) 802.3at PoE, 50-57 V DC, 25 W; (1) USB type-C, 5 V DC, 5 A
- Power supply: 802.3at PoE (pins 1, 2+/3, 6- or 4, 5+/7, 8-); AC/DC power adapter, 5 V DC, 5 A, 1.5 m cord (included)
- Supported voltage range: 90 to 264 V AC (adapter)
- Management interface: Ethernet in-band
- Networking interfaces: (1) 10/100/1000 Mbps RJ45 Ethernet; (4) 100/1,000/2,500/5,000/10,000 Mbps RJ45 Ethernet
- Services: SMB layer 2 Gigabit Ethernet switch
- ESD/EMP protection: Air: ±16 kV, contact: ±12 kV
- Button: Factory reset
- Operating temperature: -5°C to 45°C (23°F to 113°F)
- Operating humidity: 10 - 90% non-condensing
- Certifications: CE, FCC, IC

#### LEDs

- System: (1) power, blue/white; Flashing white: Bootup in progress; Flashing blue: Firmware upgrading; Steady white: Factory defaults, awaiting adoption; Steady blue: Device is adopted
- Ethernet: White: Link or activity

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

