

Item no.: UVC-G5-DOME

Camera G5 Dome

from **200,86 EUR**

Item no.: UVC-G5-DOME
shipping weight: 0.50 kg
Manufacturer: Ubiquiti

Product Description

Next-gen 2K HD PoE ceiling camera with enhanced dynamic range and low-light performance.

Features:

- 2K HD, 30 FPS camera with a 5MP CMOS sensor
- Wide-angle view (102.4°)
- Weatherproof IPX4-rated enclosure with IK08-rated vandal resistance
- Improved low-light performance and IR night vision up to 10 m
- Improved dynamic range

Mechanical

- Dimensions: Ø109.2 x 64.5 mm (Ø4.3 x 2.5")
- Weight: Without mount: 370 g (13.05 oz); With mount: 390 g (13.76 oz)
- Enclosure materials: Aluminum alloy, polycarbonate, hard-coated dome
- Mount materials: Polycarbonate, stainless steel
- Weatherproofing: IPX4
- Resistance: IK08

Optics

- Sensor: 5MP CMOS sensor
- Lens: Fixed focal length
- View angle: H: 102.4°; V: 71.4°; D: 134.3°
- Night mode: Built-in IR LED illumination and IR cut filter

Video

- Video compression: H.264, MJPEG
- Resolution: 2688 x 1512 (16:9)
- Max. frame rate: 30 FPS
- Image settings: Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

- Processor: Dual-core Arm® Cortex®-A7 based chip
- Networking interface: 10/100 MbE RJ45 port
- Max. power consumption: 5 W
- Power method: PoE
- Supported voltage range: 37–57 V DC
- LED: R/G/B/W
- Button: Factory reset
- Mounting: Wall, ceiling mount
- Operating temperature: -20°C to 40°C (-4°F to 104°F)
- Operating humidity: 0 to 90% non-condensing
- Certifications: FCC, IC, CE

Audio

- Microphone: Yes (can be disabled)
- Speaker: Yes

Software

- UniFi OS application: UniFi Protect
- Mobile app: UniFi Protect iOS™ and Android™

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

