

Item no.: UA-G2

UA-G2 - Access Reader G2, second-generation NFC card reader

from **136,54 EUR**

Item no.: UA-G2
shipping weight: 0.20 kg
Manufacturer: Ubiquiti

Product Description

Compact, second-generation NFC card reader and request-to-exit device that supports hand-wave door unlocking.

- Unlock using an NFC card or UniFi Identity mobile app
- Additional handwave unlock functionality
- Entry and exit greeting messages
- Connects to UniFi Access Hub using PoE
- IP55 weather resistance (-30°C to 45°C)

Mechanical

- Dimensions: 93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")
- Weight: 82 g (2.9 oz)
- Enclosure material: Polycarbonate, glass
- Mounting: In wall, gang box
- Weatherproofing: IP55

Hardware

- Networking interface: (1) 10/100 MbE RJ45 port
- Connectivity: BLE 4.1
- Power method: PoE
- Supported voltage range: 48 V DC
- Max. power consumption: 5 W
- ESD/EMP protection: Air: ±15 kV, contact: ±8 kV
- Sensors: Proximity sensor
- Speaker: (1) 8 ohm, 0.7 W
- LEDs: R/G/B/W
- Button: (1) Factory-reset
- NFC frequency: 13.56 MHz
- NFC read range: <30 mm
- NFC standards: ISO 14443A, 14443B, 15693
- NFC technology: NFC Tag 1, 2, 3, 4, 5; MIFARE Classic; MIFARE Plus; MIFARE Ultralight; MIFARE DESFire
- Operating temperature: -30°C to 45°C (-22°F to 113°F)
- Operating humidity: 5 to 90% non condensing
- Certifications: CE, FCC, IC

Software

- Management application: UniFi Access: Version 1.5.9 and later

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

