

Item no.: UA-G2-SK

## UA-G2-SK, Smart Door System

from **284,09 EUR**

Item no.: UA-G2-SK  
shipping weight: 0.50 kg  
Manufacturer: Ubiquiti

### Product Description

A quick start with Access with all you need for one door with one reader.

(1) UniFi Access Door Hub(1) Access Reader G2(10) UniFi Access Cards

UA-Hub-Door Mechanical

- Dimensions 174.9 x 126 x 32.9 mm (6.9 x 5 x 1.3")
- Weight 363 g (12.8 oz)
- Enclosure material
- Polycarbonate
- Mounting material
- Polycarbonate

#### Hardware

- Networking interface
- (5) 10/100/1000 Base-T
- Power method
- PoE++
- UL 294 Power-limited Class 2 PSU
- UL 60950/62368 LPS/PS2 PSU
- Max. power consumption
- Without PoE output: 30W
- With PoE output: 50W
- PoE input
- 50V DC, 1A
- PoE output
- PoE passthrough, (4) PoE, 50V DC, total 20W
- Button
- (1) Factory-reset
- LEDs
- System: white/blue
- Output relays: white
- Digital input
- Request to exit/request to enter/remote release/door position sensor
- Dry output relay
- Lock: 30V DC, 1A
- Aux: 30V DC, 1A
- Powered output relay
- Lock: 12V DC, 1A
- Aux: 12V DC, 0.33A
- 12V DC, 0.33A
- Operating environment
- Indoor use only
- Operating temperature
- 0 to 40° C (32 to 104° F)
- Operating humidity
- 5 to 95% noncondensing
- UL 294 level
- Destructive attack: Level I
- Line security: Level I
- Endurance: Level I
- Standby power: Level I
- UL 294 statement
- Compliance with IEEE 802.3 (at or af) specifications was not verified as part of UL 294.
- The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.
- CAN/ULC-60839-11-1 Grade
- Grade assignment: 1
- Certifications
- CE, FCC, IC, UL 294, CAN/ULC-60839-11-1
- Document number, and issue date and/or revision level
- UA-Hub-Door002, V01

#### LEDs

- PoE in Steady blue: Adopted/device is ready
- Steady white: Pending adoption
- Blinking white/blue: Upgrading firmware
- PoE out Off: Not connected or no data link
- Steady blue: Connected and data link on

UA-G2 Mechanical

- Dimensions 93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")
- Weight 82 g (2.9 oz)
- Enclosure material Polycarbonate, glass
- Mounting In wall, gang box
- Weatherproofing IP55

#### Hardware

- Networking interface (1) 10/100 MbE RJ45 port
- Connectivity BLE 4.1
- Power method PoE
- Supported voltage range 48V DC
- Max. power consumption 5W
- ESD/EMP protection Air:  $\pm 15\text{kV}$ , contact:  $\pm 8\text{kV}$
- Sensors Proximity sensor
- Speaker (1) 8 ohm, 0.7W
- LEDs R/G/B/W
- Button (1) Factory-reset
- NFC frequency 13.56 MHz
- NFC read range < 30 mm
- NFC standards ISO 14443A, 14443B, 15693
- NFC technology NFC Tag 1,2,3,4,5
- MIFARE Classic
- MIFAREPlus
- MIFARE Ultralight
- MIFARE DESFire
- Operating temperature -30 to 45° C (-22 to 113° F)
- Operating humidity 5 to 90% noncondensing
- Certifications CE, FCC, IC

#### UA-Card Mechanical

- Dimensions 85.6 x 53.98 x 0.84 mm (3.37 x 2.13 x 0.03")
- Weight 5 g (0.18 oz)
- Format ISO 7810 ID-1
- NFC frequency 13.56 MHz
- NFC technology ISO/IEC 14443 Type A
- MIFARE DESFire
- UniFi Access Proprietary Security Protocol

#### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

