

Item no.: UA-SK-ELEVATOR

**UA-SK-ELEVATOR - UA-SK-ELEVATOR, Starter Kit**from **885,37 EUR**

Item no.: UA-SK-ELEVATOR

shipping weight: 0.70 kg

Manufacturer: Ubiquiti

 **Product Description**

Connection to lift reader via PoE to authorise floor selection by the user. Support for up to 18 floors and digital inputs for car status and emergency.

UA-Hub-Elevator Mechanical- Dimensions 129.3 x 244.7 x 33.6 mm (5.1 x 9.6 x 1.3")- Weight 537 g (1.2 lb)- Housing material polycarbonate- Mounting material polycarbonateUA-Hub-ElevatorHardware- Network interface (4) 10/100/1000 Base-T- Management interface (1) 10/100/1000 Base-T- Power supply method PoE+- Max. Power consumption 7 W (without PoE output)- PoE input (1) PoE+-, 50 V DC, 1.2 A- PoE output PoE passthrough, (4) PoE, 50 V DC, 42 W in total- ESD/EMP protection air: ±8 kV, contact: ±4kV- Digital input (6) car position; up/down/stop/full/door open/door closed; (1) emergency- Outputs (18) relays; rated 30V DC/2A- LEDs system: white/blue/red- Output relays: white- Buttons (1) factory reset; terminal blocks- Operating temperature -10 to 40° C (14 to 104° F)- Operating humidity 5 to 95% non-condensing- Certifications CE, FCC, ICUACC-Extender-2Wire-Tx/RxMechanical- Dimensions 40 x 105 x 25 mm (1.6 x 4.1 x 1")- Weight PoE in: 77 g (2.7 oz)- PoE out: 79 g (2.8 oz)- Housing material polycarbonate- Mounting material polycarbonateUACC-Extender-2Wire-Tx/RxHardware- Network interface (1) 10/100 MbE; (1) Homeplug AV- Management interface (1) 10/100 MbE- Power supply method PoE+- Max. Power consumption 3W (without PoE output)- PoE input (1) PoE+-, 50V DC, Max. 1.2A- PoE output (1) PoE+, 48V DC, 0.72A- ESD/EMP protection air: ±8kV, contact: ±4kV- LED White- Operating temperature -10 to 40° C (14 to 104° F)- Operating humidity 5 to 95% non-condensing- Certifications CE, FCC, ICUA-G2Mechanical- Dimensions 93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")- Weight 82 g (2.9 oz)- Housing material polycarbonate, glass- Mounting In the wall, in the control box- Weather protection IP55UA-G2Hardware- Network interface (1) 10/100 MbE RJ45 port- Connectivity BLE 4.1- Power supply method PoE- Supported voltage range 48V DC- Maximum power consumption 5W- ESD/EMP protection air: ±15kV, contact: ±8kV- Sensors Proximity sensor- Speaker (1) 8 Ohm, 0.7W- LEDs R/G/B/W- Button (1) factory reset- NFC frequency 13.56 MHz- NFC read range < 30 mm- NFC standards ISO 14443A, 14443B, 15693- NFC technology NFC Tag 1,2,3,4,5; MIFARE Classic: MIFAREPlus: MIFARE Ultralight; MIFARE DESFire- Operating temperature -30 to 45° C (-22 to 113° F)- Operating humidity 5 to 90% non-condensing- Certifications CE, FCC, ICUA-CardMechanical- Dimensions 85.6 x 54 x 0.8 mm (3.4 x 2.1 x 0.03")- Weight 5 g (0.18 oz)- Format ISO 7810 ID-1- NFC frequency 13.56 MHz- NFC technology ISO/IEC 14443 Type A- MIFARE DESFire- UniFi Access Proprietary Security ProtocolScope of delivery- (1) Elevator Hub- (1) G2 Reader- (2) 2-wire PoE Extender- (10) Access Cards

 **Specifications**

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

