

Item no.: 384587

CSM-200-1213 - Unmanaged 10/100BaseT(X) to 100BaseFX slide-in modules**from 203,35 EUR**Item no.: 384587
shipping weight: 0.30 kg
Manufacturer: MOXA **Product Description**

The CSM-200 plug-in media converters from Ethernet to fibre optic are designed for the NRack System™. The modules provide media conversion from 10/100BaseT(X) to 100BaseFX (SC/ST ports) and can be installed in any NRack System™ enclosure. Ethernet interface- 10/100BaseT(X) ports (RJ45 connector): 1- 100BaseFX ports (multi-mode SC connector): CSM-200-1213: Multi-mode ST connector- 100BaseFX ports (multi-mode SC connector): CSM-200-1214: Multi-mode SC connector- 100BaseFX ports (single-mode SC connector): CSM-200-1218: Single-mode SC connector- Magnetic insulation protection: 1.5 kV (built-in)- Standards: IEEE 802.3u for 100BaseT(X) and 100BaseFX- Fibre optics: Read more Performance parameters- Input current: 180 mA @ 12 VDC- Input voltage: 12 VDC- Overload current protection: Supported- Power consumption: 180 mA @ 12 VDC Physical characteristics- Dimensions: 86.8 x 124.3 x 21 mm (3.42 x 4.89 x 0.83 in.)- Weight CSM-200-1213: 115 g (0.25 lb)- Weight CSM-200-1214/1218: 125 g (0.28 lb) Environmental Conditions- Operating Temperature: 0 to 55°C (32 to 131°F)- Storage Temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- EMC: EN 55032/24- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV, IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m, IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV, IEC 61000-4-5 Surge: Power: 2 kV(AC), 1 kV(DC), IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m, IEC 61000-4-8 PFMF, IEC 61000-4-11- Environmental testing: IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-3- Safety: EN 60950-1, UL 60950-1- Vibration: IEC 60068-2-6MTBF- Time: 1,454,560 hours- Standards: Telcordia (Bellcore), GB

 Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

