

Item no.: BR1200ELCD

BR1200ELCD - Line-Interactive UPS 1200 VA / 720 W

from **189,27 EUR**

Item no.: BR1200ELCD
 shipping weight: 9.80 kg
 Manufacturer: CyberPower



Product Description

CyberPower BR1200ELCD - Line-Interactive UPS 1200 VA / 720 W The BRICs LCD Series UPS with LCD can supply clean and stable power to protect your equipment. The included PowerPanel(R) Personal Edition management software showcases the feature-rich abilities of this UPS such as input/output power voltage readings, self-diagnostics, scheduled shutdown, and approximate battery back-up time reading. These UPS units can be placed in either a horizontal or wallmount position to make the most of your space. With Energy-Saving Technology, BRIC LCD Series' UPS can save up to 75% of electricity and save your electricity bill. You can easily charge AA/AAA batteries via USB with a battery charger. Features & Benefits:

- GreenPower UPS(TM) Technology: Energy-Saving UPS
- Microprocessor-based full digital control
- Automatic Voltage Regulator (AVR)
- EMI, RFI, Surge and lightning protection
- Phone / Fax / Modem / DSL / Network protection
- Power Management software included
- Scheduled shutdown
- Auto restart / Auto charge
- Horizontal / Wallmount use
- USB connectivity ports
- Compact design with highest power output
- LCD Status Monitor
- Save up to 75 % of electricity
- External AA/AAA battery charger included *(batteries excluded)
- Cable collector included

General

- UPS Topology: Line-interactive
- Energy Saving: Yes
- Input:
 - Voltage: 220/230/240 Vac
 - Input Voltage Range: 165 - 290 V ac
 - Rated Input current: 5.45 A
 - Plug Type: Schuko
 - Input Frequency Range: 45 ~ 65 Hz
- Output:
 - VA: 1200
 - Watts: 720
 - On Battery Waveform: Simulated Sine Wave
 - On Battery Voltage: 220 - 240 V ac
 - Automatic Voltage Regulation (AVR): Single Boost / Single Buck
 - On Battery Frequency: 50/60Hz +/- 1%
 - Outlets - Total: 8
 - Outlet Type: Schuko
 - Outlets - Battery & Surge Protected: 4
 - Outlets - Surge-Only Protected: 4
 - USB Charging Ports: Yes
 - Transfer Time: 4ms
- Battery:
 - Runtime at 60 W (min): 80
 - Runtime at 90 W (min): 51
 - Battery Type: Sealed Lead Acid
 - Battery Quantity: 2
 - User Replaceable: Yes
 - Hot-Swappable: Yes
 - Typical Recharge Time: 8 Hours
 - Replacement Battery Pack: RBP0063
 - Replacement Battery Pack Quantity: 2
- Surge Protection and Filtering:
 - Surge Suppression: 125 Joules (L-N)
 - Phone / Network Protection RJ11/RJ45: 1-In, 1-Out (Combo)

Physical

- Management & Communications:
 - LCD Control Panel: Yes
 - HID Compliant USB Port: Yes
 - LED Indicators: Yes
 - Audible Alarms: On Battery, Low Battery, Overload, Fault
 - Software: PowerPanel(R) Personal Edition
- Form Factor: Brick
- Dimensions (W x H x D) (mm): 166 x 118 x 288
- Weight (kg): 8.2

Environmental

- Operating Temperature: + 32 °F to 104 °F / 0 °C to 40 °C
- Operating Humidity: 0 % - 90 % non-condensing
- Operating Elevation: 0-10000 feet (0-3000 meters)
- Storage Temperature: - 4 °F to 122 °F / -20 °C to 50 °C
- Storage Relative Humidity: 0 % - 90 %
- Online Thermal Dissipation: 137 BTU/hr

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

