

MCE630 - Maclean LED floodlight with motion sensor, slim 30W, 2400lm, neutral white (4000K), IP44

from **11,26 EUR**

Item no.: 382078 shipping weight: 0.40 kg Manufacturer: Maclean Brackets

Product Description

High-quality energy-saving and reliable light source with long life.IP44 protection class protects the device from water jets, which allows the floodlight to be used as an outdoor lamp. Adjustable handle allows you to adjust the angle of illumination.Ideal for lighting entrances, driveways, terraces, garden paths, backyards, as well as in workshops, warehouses, garages, basements, etc.Built-in PIR motion sensor and twilight sensor guarantee stable and very fast operation of the lamp. No need to install expensive external sensors. The light will automatically turn on when motion is detected within the range of the sensor and turn off after the selected time has elapsed.Specifications- Power supply: 220-240V- Power frequency: 50/60 Hz- Protection class: IP44- Power: 30 W- Luminous flux: 2400 Im- Lifetime: 50000 hours- Number of on/off cycles: 20000- Illumination angle: 120° - Luminaire suitable for indoor and outdoor installation- Temperature range in which the luminaire can operate: -20° C to $+35^\circ$ C- Light color: neutral white- Color temperature: 4000K- Ambient light sensitivity (day/night): <3-2000LUX (adjustable)- Time delay: min. Seec ($\pm 2sec$) - max. 5min ($\pm 1mi$) (adjustable)- Installation heights: $1.8 \cdot 2.5m$ - Detection range: 120° - Sensitivity/distance of detection: 2-10m (adjustable)- Does not work with dimmer- Energy efficiency class (as of 01/09/2021): F- Cable length 12cm- Cable terminated with terminal block mounting lugsThe set includes- LED floodlight with motion sensor Maclean MCE630 NW- User manual- Manufacturer's packagingFeatures- Energy-efficient LEDs- Easy and quick installation- Power: 30W- Light color: neutral white- High quality workmanship- Very thin housing - 30 mm- Light output: 2400 lumens- Adjustable twilight sensor- Built-in motion sensor- Detection distance: 2-10m (adjustable)- With IP44 rating, the floodlight can be mounted outdoors

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

