

Item no.: 384544

SS14HV.30.2RT - QuSector S24-14HV-30-2 2x RPTNC

 from **86,18 EUR**

 Item no.: 384544
 shipping weight: 2.50 kg
 Manufacturer: QuWireless


Product Description

QuSector S24-14HV-30-2 offers a 30 degrees, 14dBi gain signal with two 2.4GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector S24-14HV-30-2 is a single band, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz with 14dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes with two 70cm (28inch) cables. The antenna comes with 2*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors. Wi-Fi SPECIFICATION FREQUENCY- 2.3 - 2.7GHz GAIN- 14 dBi SWR- < 1.80 BEAMWIDTH- 30°/30° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- > 32dB FRONT-TO-BACK- > 30dB MAX INPUT POWER- 50WDC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 2x RPTNC OUTER DIMENSIONS- 29.2 x 48.6 x 10.6 cm- 11.5 x 19.13 x 4.17 inch WEIGHT- 2.5 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

Specifications

 Scan this QR code to
 view the product

 All details, up-to-date
 prices and availability
