

Item no.: 384305

APBM3MO - QuMax Omni for Peplink MAX BR1 Mini (HW3)

from **138,06 EUR**

Item no.: 384305
 shipping weight: 1.80 kg
 Manufacturer: QuWireless



Product Description

INTEGRATED MULTI-BAND 5G OMNI ANTENNA + WIFI OMNI ANTENNA + GPS ANTENNA + PLACE TO INSTALL PEPLINK MAX BR1 MINI (HW3) & M2M (ALL-IN-ONE) QuMax Omni all-in-one antenna for Peplink MAX BR1 Mini (HW3) & M2M router is a perfect outdoor device for mobile and fixed installations like industrial, public, CCTV, hotspots, yachts, boats, campers, RV etc. It has embedded omni 5G, Wi-Fi and GPS antenna. If you use MAX BR1 Mini (HW3) or M2M with QuMax Omni antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

5G / LTE SPECIFICATION
 FREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.7 GHz- 5.2 - 6.0 GHz
 GAIN- 617 - 960 MHz : 3 dBi- 1.7 - 2.7 GHz : 4 dBi- 3.3 - 4.7 GHz : 4.5 dBi- 5.2 - 6.0 : 2.5dBi
 SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106
 SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n47, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256
 VSWR- <1.80, max <2.00
 BEAMWIDTH- 360°/35° +/- 5°
 POLARIZATION- Vertical
 IMPEDANCE- 50 Ω
 WI-FI SPECIFICATION
 FREQUENCY- 2.4 - 2.5 GHz- 5.0 - 6 GHz
 GAIN- 2.4 - 2.5 GHz: 6 dBi- 5.0 - 6.0 GHz: 7 dBi
 VSWR- <1.70, max <2.00
 BEAMWIDTH- 360°/25° +/- 5°
 POLARIZATION- Vertical
 IMPEDANCE- 50 Ω
 MECHANICAL SPECIFICATION
 MATERIAL- BS, aluminum, PTFE, Fiberglass
 INGRESS PROTECTION- IP67
 CONNECTOR TYPE- RJ45
 DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch
 WEIGHT- 1.8 kg- 3.97 lbs
 OPERATING TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

