

Item no.: 384356

AO5G4-GN - QuOmni 5GLTE Global MIMO 4x4, Nf

from **124,18 EUR**

Item no.: 384356
 shipping weight: 1.50 kg
 Manufacturer: QuWireless



Product Description

Omnidirectional ultra wideband 5G/LTE MIMO 4x4 antenna QuOmni 5G/LTE omnidirectional MIMO 4x4 is ultra wideband LTE Outdoor antenna. It's primary designed for LTE/5G/3G/2G devices which require high efficiency connections. The antenna covers many LTE bands including the new Extended LTE Band 71, frequencies: 617 - 6000MHz. The mounting bracket allows the antenna to be installed on the buildings (on the pole or on the wall) as the client antenna or on the moving points like trains, buses, lorries, yachts, boats to receive Internet by LTE/5G/3G/2G. It's ideal solution to use with all industrial and domestic 4x4 LTE modems and routers like: Teltonika, DIGI, Mikrotik, Robustel, Cisco, etc. 5G / LTE ANTENNA SPECIFICATION- Frequency: 617 - 960 MHz, 1.7 - 2.7 GHz, 3.3 - 4.7 GHz, 5.2 - 6.0 GHz- Gain: 617 - 960 MHz : 3 dBi, 1.7 - 2.2 GHz : 4 dBi, 3.3 - 4.7 GHz : 4.5 dBi, 5.2 - 6.0 GHz : 2.5dBi- Supported LTE Bands: 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106- Supported 5G Bands: n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n47, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256- VSWR: <1.80, max <2.00- Beamwidth: 360°/35° ±5°- Polarisation: Vertical- Impedance: 50 ΩMECHANICAL SPECIFICATION- Materials: ABS, aluminum, PTFE- Connector Type: Nf- Ingress Protection: IP67- Dimensions: 160 x 160 x 240 mm (6.3 x 6.3 x 9.45 inch)- Weight: 1.5 kg (3.31 lbs)- Operating Temperature: from -40°C to 80°C (from -40°F to 176°F)- Mast Diameter: 40-60 mm (1.57-2.36 inch)

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

