

Item no.: 384535

## SS19HV.20.2RS - QuSector S24-19HV-20-2 2x RPSMA

 from **112,12 EUR**

 Item no.: 384535  
 shipping weight: 2.50 kg  
 Manufacturer: QuWireless


### Product Description

QuSector S24-19HV-20-2 offers a 90 degrees, 19dBi gain signal with two 2.4GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector S24-19HV-20-2 is a single band, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz with 19dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in with 2\*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors. QuSector S24-19HV-20-2 was designed to be a perfect match for your access point.

Wi-Fi SPECIFICATION  
 FREQUENCY- 2.3 - 2.7GHz  
 GAIN- 14 dBi  
 VSWR- < 1.80  
 BEAMWIDTH- 30°/30°  
 POLARIZATION- Horizontal- Vertical  
 IMPEDANCE- 50 Ω  
 SEPARATION BETWEEN CONNECTORS- > 32dB  
 FRONT-TO-BACK- > 30dB  
 MAX INPUT POWER- 50W  
 DC GROUND- Yes  
 MECHANICAL SPECIFICATION  
 MATERIAL- ABS  
 CONNECTOR- 2xRPSMA  
 OUTER DIMENSIONS- 29.2 x 48.6 x 10.6 cm- 11.5 x 19.13 x 4.17 inch  
 WEIGHT- 2.5 kg  
 OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F  
 MOUNTING KIT  
 DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch  
 REGULATION RANGE- +/- 30°  
 MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch  
 MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts  
 MOUNTING PLACE- Wall or ceiling or mast

### Specifications

 Scan this QR code to  
 view the product

 All details, up-to-date  
 prices and availability
