

Item no.: 384530

SS14HV.30.4RT - QuSector S14HV-30-5 4x RPTNC

 from **156,22 EUR**

 Item no.: 384530
 shipping weight: 1.80 kg
 Manufacturer: QuWireless


Product Description

QuSector 14HV-30-4 Wi-Fi 6e offers a 30 degrees, 14dBi gain signal with two 2.4GHz and 5GHz+7GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector 14HV-30-4 Wi-Fi 6e is a concurrent dual band, H&V polarity, MIMO 4x4 panel antenna. It operates at 2.4GHz and 5-7.125GHz simultaneously with 14dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. Wide frequency range (2.4-2.5GHz & 5.1-7.125GHz) helps to find suitable frequency for the most effective operation. The antenna comes with four 70cm (28inch) cables terminated with RPTNC, RPSMA or Nm connectors. Wi-Fi SPECIFICATION FREQUENCY- 2.4 - 2.5GHz- 5.1 - 7.125GHz GAIN- 14 dBi SWR- < 2.00 BEAMWIDTH- 30°/30° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- > 25dB FRONT-TO-BACK- > 20dB- > 25dB MAX INPUT POWER- 50W DC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 4x RPTNC OUTER DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch WEIGHT- 1.8 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

