

Item no.: 384445

## S14HV.90.2NM - QuSector 14HV-90-2 Wi-Fi 6E 2x Nm

 from **156,22 EUR**

 Item no.: 384445  
 shipping weight: 1.80 kg  
 Manufacturer: QuWireless


### Product Description

QuSector 14HV-90-2 offers a 90 degrees, 14dBi gain signal with two RP-SMA 2.4GHz and 5GHz+7GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector 14HV-90-2 is a dual band, concurrent, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz and 5GHz+7GHz. It is a futureproof solution with Wi-Fi 6E and Wi-Fi 7 support. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in three configurations: with 2\*70cm (28inch) cables terminated with Nm, RPSMA and RPTNC connectors. QuSector 14HV-390-2 was designed to be a perfect match for your access point. Wi-Fi

**SPECIFICATION**  
 FREQUENCY- 2.4 - 2.5 GHz- 5.0 - 7.125 GHz  
 GAIN- 12 dBi- 14 dBi  
 VSWR- < 2.00  
 BEAMWIDTH- 90°/30°- 90°/16°  
 POLARIZATION- Horizontal- Vertical  
 IMPEDANCE- 50 Ω  
 SEPARATION BETWEEN CONNECTORS- >30 dB  
 FRONT-TO-BACK- > 20dB- >25dB  
 MAX INPUT POWER- 50W  
 DC GROUND- Yes  
 MECHANICAL

**SPECIFICATION**  
 MATERIAL- ABS  
 CONNECTOR- 2xNM  
 OUTER DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch  
 WEIGHT- 1.8 kg  
 OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F  
 MOUNTING KIT  
 DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch  
 REGULATION RANGE- +/- 30°  
 MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch  
 MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts  
 MOUNTING PLACE- Wall or ceiling or mast

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

