

Item no.: 384447

S12HV.30.2RS - QuSector 12HV-30-2 2x RPSMA

 from **156,22 EUR**

 Item no.: 384447
 shipping weight: 1.80 kg
 Manufacturer: QuWireless


Product Description

QuSector 12HV-30-2 offers a 30 degrees, 12dBi gain signal with two 2.4GHz+5GHz connectors. It is a perfect indoor and outdoor device for industrial installations.-End of Life- QuSector 12HV-30-2 is a dual band, concurrent, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz+5GHz with 12dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in the following configurations: with 2*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors. QuSector 12HV-30-2 was designed to be a perfect match for your access point.WE REGRET TO INFORM YOU THAT THE PRODUCT HAS REACHED ITS END OF LIFE (EOL). A NEWER AND BETTER VERSION IS NOW OUT. CHECK IT OUT HERE: QuSector 14HV-30-2 Wi-Fi 6eWi-Fi SPECIFICATIONFREQUENCY- 2.4 - 2.5GHz- 5.1 - 5.9GHzGAIN- 12 dBiVSWR- < 2.00BEAMWIDTH- 35°/35°POLARIZATION- Horizontal- VerticalIMPEDANCE- 50 ΩSEPARATION BETWEEN CONNECTORS- >25dBFRONT-TO-BACK- > 20dB- > 25dBMAX INPUT POWER- 50WDC GROUND- YesMECHANICAL SPECIFICATIONMATERIAL- ABSCONNECTOR- 2xRPSMAOUTER DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inchWEIGHT- 1.8 kgOPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°FMOUNTING KITDIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inchREGULATION RANGE- +/- 30°MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inchMATERIAL- Polyamide with fiberglass + galvanized steel U-BoltsMOUNTING PLACE- Wall or ceiling or mast

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

