

Item no.: 329929

## SIP-T53W - SIP-T53W - IP Phone with a 3.7-inch graphical adjustable LCD Display

from **129,24 EUR**

Item no.: 329929  
 shipping weight: 1.30 kg  
 Manufacturer: Yealink



### Product Description

SIP-T53W - IP Phone with a 3.7-inch graphical adjustable LCD Display

Prime Business Phone to Deliver Optimum Desktop Productivity

Especially designed for busy executives and professionals, Yealink SIP-T53W is an easy-to-use Prime Business Phone with an adjustable 3.7-inch graphical LCD that you can easily and flexibly find the comfortable viewing angle according to the personal and environmental needs. With the built-in Bluetooth 4.2 and the built-in dual band 2.4G/5G Wi-Fi, the SIP-T53W IP Phone ensures you to keep up with the modern wireless technology and take the first chance in the future wireless age. Its built-in USB 2.0 port allows for USB recording or a direct wired/wireless USB headset or up to three Yealink EXP50 expansion modules connection. Benefitting from these features, the Yealink SIP-T53W is a powerful and expandable office phone that delivers optimum desktop efficient and productivity.

#### Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Audio codec: Opus, G.722, PCMA, PCMU, G.729A/B, G.726, G.723.1, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

#### Phone Features

- 12 VoIP accounts
- Call hold, mute, DND, redial, call return, auto answer
- One-touch speed dial, call forward, call waiting, call transfer
- Group listening, hotline, SMS, emergency call
- 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, XML Browser, Action URL/URI
- RTPP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Built-in dual band Wi-Fi: Network standard: IEEE 802.11a/b/g/n/ac; Transmission rate: Up to 433 Mbps (dynamic); Frequency range: 2.4 GHz/5.0 GHz
- Built-in Bluetooth 4.2 for: Bluetooth headsets; Contact synchronization; Bluetooth call
- USB port (2.0 compliant) for: Wired/wireless USB headset; USB call recording through USB flash drive; Expansion module EXP50 (up to 3)
- Content Sharing (via Yealink VCD)(1)
- Enhanced DSS key

#### Display and Indicator

- 3.7" 360 x 160-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

#### Physical Features

- Color: Classic grey
- Wall mountable (optional)
- External Yealink AC adapter (optional): AC 100~240 V input and DC 5 V/1.2 A output
- USB output currency: 5 V, 500 mA
- Power consumption (PSU): 1.3 - 2.3 W
- Power consumption (PoE): 1.8 - 3.1 W
- Dimension (WxDxH): 212 x 210.6 x 174.5 mm
- Operating humidity: 10~95%
- Operating temperature: -10°C ~ 50°C (+14°F ~ 122°F)

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

