

Item no.: 311551

VARIA 5 dBi Clip Antenna Set + Magnetic Mount for FRITZ!Box, Speedport

from **25,95 EUR**

Item no.: 311551
shipping weight: 0.13 kg
Manufacturer: VARIA Group



Product Description

VARIA 5 dBi Clip Antenna Set + Magnetic Mount The VARIA modification set is for FRITZ!Box and Speedport router. With this high-performance antenna set you can enhance the strength of the outgoing signal as well as the receiver sensitivity. The greater signal strength and the improved sensitivity improve the reliability of communication over short ranges, because the signals can be received more clearly, which in turn reduces retransmission caused by weak signal strength. This professional high-performance antenna (with clip connector - FRITZ!Box or Speedport) is especially well suited to receive a clear signal in difficult and hard-to-reach locations. It is also ideal for larger areas like storage facilities and wireless hotspots - all the places where you need a greater range for your wireless network. Functions:

- Improvement of the radio signal of your wireless devices (2.4 GHz)
- Omnidirectional spread (receive signals in a 360° angle)
- Simple setup, no installation required

In the box:

- 1x CLIP pigtail for FRITZ!Box and Speedport router with clip connector
- 1x magnetic mount with 1.5 m cable
- 1x professional 5 dBi high-speed WLAN clip antenna for FRITZ!Box and Speedport
- Quick start guide
- Fact sheet "Antenna Adjustment"

VARIA Clip Pigtail

- Connector: RP-SMA female connector (reverse polarity) to U.FL CLIP
- Cable type: RG178 low loss cable
- Cable length: ca. 25 cm
- RoHS compliant

Magnetic Mount

- Connector: RP-SMA male connector (reverse polarity)
- Cable type: HDF100 low loss cable
- Cable length: ca. 1.5 m
- RoHS compliant

WLAN Antenna

- Gain: 5 dBi
- Frequency: 2.4 GHz - 2.5 GHz
- Voltage standing wave ratio (VSWR): < 2
- Polarisation: Linear/Vertikal
- Direction: Omnidirectional
- Resistance: 50 ohm
- Connector: RP-SMA
- Measurements: 15 mm x 250 mm
- Weight: 48 g
- Color: Black
- Operating temperature: -20 °C to 60 °C
- Storage temperature: -30 °C to 75 °C
- Operating humidity: 0 % to 85 % (non condensing)

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

