

Item no.: 384504

## AR1511SP - QuSpot with PoE Splitter for Robustel R1511P

from **130,28 EUR**

Item no.: 384504  
shipping weight: 1.50 kg  
Manufacturer: QuWireless



### Product Description

INTEGRATED MULTI-BAND 5G OMNI ANTENNA + WI-FI 6E OMNI ANTENNA + POE SPLITTER + PLACE TO INSTALL ROBUSTEL R1511P (ALL-IN-ONE) QuSpot antenna for Robustel R1511P router is a perfect outdoor device for mobile and fixed installations like industrial, CCTV, hotspots, yachts, boats, campers, RV etc. It has embedded omni 5G and omni Wi-Fi 6E antenna. If you use R1511P with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. Wi-Fi 6E support! The set contains a PoE splitter, allowing you to split data and power from a single Ethernet cable and maintain gigabit transfer speeds while protecting the LAN port from damage caused by overvoltage, short circuit or improper connection. 5G / LTE ANTENNA SPECIFICATION FREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.7 GHz- 5.2 - 6.0 GHz GAIN- 617 - 960 MHz : 3 dBi- 1.7 - 2.2 GHz : 4 dBi- 3.3 - 4.7 GHz : 4.5 dBi- 5.2 - 6.0 GHz : 2.5 dBi SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106 SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n47, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256 VSWR- <1.80, max <2.00 BEAMWIDTH- 360°/35° ±5° POLARIZATION- Vertical IMPEDANCE- 50 Ω WI-FI ANTENNA SPECIFICATION FREQUENCY- 2.4 - 2.5 GHz- 5.0 - 7.2 GHz GAIN- 2.4 - 2.5 GHz: 6 dBi- 5 GHz: 7.5 dBi- 7 GHz: 7.5 dBi VSWR- < 1.50, max < 2.00 BEAMWIDTH- 360°/25° POLARIZATION- Vertical IMPEDANCE- 50 Ω MECHANICAL SPECIFICATION MATERIALS- ABS, aluminum, PTFE CONNECTOR TYPE- RJ45 INGRESS PROTECTION- IP67 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch WEIGHT- 1.5 kg- 3.31 lbs OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

