

Item no.: 384500

AX50S - QuSpot for RUTX50

from 170,08 EUR

 Item no.: 384500
 shipping weight: 1.50 kg
 Manufacturer: QuWireless


Product Description

INTEGRATED MULTI-BAND LTE & 5G OMNI ANTENNA + WI-FI OMNI ANTENNA + GPS PLACE TO INSTALL TELTONIKA RUTX50 (ALL-IN-ONE) QuSpot for RUTX50 is an outdoor antenna designed to provide reliable wireless connectivity in a variety of environments. This product is an all in one solution that integrates a high gain omnidirectional 5G and Wi-Fi antennas with RUTX50 into a single IP67 enclosure. Such integration allows implementation of new outdoor RUTX50 solutions. QuSpot for RUTX50 is an ideal solution for outdoor wireless connectivity in moving applications such as transportation, yachting, boats and camping but also city centres with high signal density. 5G antenna specification FREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.3 GHz GAIN- 617 - 960 MHz : 2 dBi- 1.7 - 2.7 GHz : 4 dBi- 3.3 - 4.3 GHz : 4.5 dBi SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 1067, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, n77, n78, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101 SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256 VSWR- <2.00, max <2.50 BEAMWIDTH- 360°/25° ±5° POLARIZATION- Vertical IMPEDANCE- 50 Ω Wi-Fi antenna specification FREQUENCY- 2.4 - 2.5 GHz- 4.7 - 6 GHz GAIN- 2.4 - 2.5 GHz : 6 dBi- 4.7 - 6 GHz : 7.5 dBi VSWR- <1.70, max <2.00 BEAMWIDTH- 360°/25° ±5° POLARIZATION- Vertical IMPEDANCE- 50 Ω Mechanical specification MATERIALS- ABS, aluminum, PTFE CONNECTOR TYPE- RJ45 INGRESS PROTECTION- IP67 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch WEIGHT- 1.5 kg- 3.31 lbs OPERATING TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

