

Item no.: 384509

AMT115GS - QuSpot for MikroTik RBM11G 5G

from **103,04 EUR**

Item no.: 384509
 shipping weight: 1.50 kg
 Manufacturer: QuWireless



Product Description

INTEGRATED MULTI-BAND LTE & 5G OMNI ANTENNA + PLACE TO INSTALL MIKROTIK RBM11G (ALL-IN-ONE) QuSpot is an outdoor antenna designed to provide reliable wireless connectivity in a variety of environments. This product is an all in one solution that integrates a high gain omnidirectional 5G/LTE 4x4 MIMO antennas with MikroTik board into a single IP67 enclosure. Such integration allows implementation of new outdoor solutions. Four ultra wide band 5G/LTE antennas make an universal solution and enable to integrate MikroTik boards in many different combinations, based on RBM11G. QuSpot for MikroTik is an ideal solution for outdoor wireless connectivity in moving applications such as transportation, yachting, boats and camping but also city centres with high signal density. 5G antenna specification

FREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.3 GHz

SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, n77, n78, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101

SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256

GAIN- 617 - 960 MHz : 2 dBi- 1.7 - 2.7 GHz : 4 dBi- 3.3 - 4.3 GHz : 4.5 dBi

SWR- <2.00, max <2.50

BEAMWIDTH- 360°/25° ±5°

POLARIZATION- Vertical

IMPEDANCE- 50 Ω

Mechanical specification

MATERIALS- ABS, aluminum, PTFE

CONNECTOR TYPE- RJ45

INGRESS PROTECTION- IP67

DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch

WEIGHT- 1.5 kg- 3.31 lbs

OPERATING TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F

MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

